



Installation - GX Joggle Gutter


GX Joggle gutters are a press formed eaves drainage system with sharply defined box profile. Gutters are supported by internal top straps and directly fixed to the fascia board. The Joggle method of gutter jointing uses an integral internal union or formed spigot which is wet sealed using silicone sealant.




GX Joggle fixes to fascia using a heavy gauge top strap.




1. Use a string line or laser to set out gutter lines. (GX Joggle must be laid level).




2. Position angles, mark fixing positions and pilot 3.5mm diameter holes, fit top strap and loosely fix using No12 x 38mm roundhead screws.




3. Plumb line outlet position with gullies at ground level, pilot 3.5mm diameter holes, fit top strap and loosely fix using No12 x 38mm roundhead screws.




4. Position gutter lengths allowing for 4mm expansion joints. Mark fixing positions and pilot 3.5mm diameter holes.




5. Thoroughly degrease all jointing surfaces and apply two 6mm beads of DOW 791 silicone sealant either side of and around the slotted fixing holes.




6. Secure joints with aluminium M6 x 12mm nuts, bolts and washers provided taking care not to over tighten or displace sealant from within the joint.



7. Cone-off the exposed bolts, studs and nuts inside the gutter with a generous application of silicone sealant.



8. Align gutter lengths correctly for final positioning. Engage top straps and fix back securely to fascia.



9. Tool off excess silicone around the union joint and from visible external surfaces.